



## **InterXect with Extend Panels - Technical Data**

### **Contact**

StarwallUSA  
5200 South Sprinkle Rd  
Kalamazoo, MI 49002  
Phone: (269) 488-2752  
Fax: (269) 488-2754  
Web: [www.starwallusa.com](http://www.starwallusa.com)

### **GENERAL PRODUCT DESCRIPTION**

#### **Recommended Uses**

INTERXECT EXTEND™ Durable Demising Wall is a flexible, demountable, wall panel and stud system ideally suited for demising, offices, medical patient rooms, and commercial architectural settings, etc.

#### **Product Composition**

*Wall Panels* - High definition printed artwork is bonded directly to recycled 5/8" Type X gypsum using permanent thermosetting adhesive.

*Sound Insulation* - HealthGuard™ made from recycled PET fiber such as reclaimed soda bottles, carpet fiber, etc.

*Stud And Track Components* - 24 gauge high recycled content cold rolled commercial quality galvanized steel.

#### **Basic Limitations**

EXTEND™ Durable Demising Wall is for non-structural demising or decorative applications. EXTEND™ Durable Demising Wall is not intended for use as a structural component in any application regarding safety, support for humans, or in applications where metal fatigue or failure could result in injury, death, or ancillary property damage.

EXTEND™ Durable Demising Wall panels should not be subjected to temperatures higher than 150°F for sustained periods of time as glossing of the decorative artwork finish can occur.

#### **Finishes**

EXTEND™ Durable Demising Wall is available in 25+ standard finishes. Hundreds of custom finishes are available. Wood Finishes, Solid Color Finishes, and Abstract Finishes are available. Please visit [www.starwallusa.com](http://www.starwallusa.com) for available finishes.



### Custom Finish Availability

Due to the nature of the printing process, custom EXTEND™ Durable Demising Walls are subject to sizable minimum order quantities. Please contact your local EXTEND™ distributor for additional information.

EXTEND Panel Sizes	Corners & Trim Molding Sizes
96", <b>108"</b> , <b>120"</b> Panels x 48" Width	10' Lengths

*\*Standard Sizes (in Bold Italics)*

### Typical Properties of Panel & Trim Surface

Test	Standard	EXTEND Surface
<b>Fire Rating</b>	ASTM E-84 UL-723	Class A
<b>Color Fastness</b>	Xenon-meter	No Appreciable Change 300hrs
<b>Heat Stability</b>	NEMA 11-14-95	No Appreciable Change
<b>Chemical Resistance</b> Benzene Ethanol n-Hexane HCL - 10% NaOH - 10% H <sub>2</sub> SO <sub>4</sub> - 10% Ca(OH) <sub>2</sub> - Saturated	NEMA 11-14-95	No Appreciable Change
<b>Solvent Resistance</b> Toluene MEK Ethyl Acetate Acetone	NEMA 11-14-95	Some Change
<b>Abrasion Resistance</b>	ASTM-D1044	500 Cycles Minimum
<b>Impact Resistance</b>	8 oz Steel Ball Dropped 2"	No Appreciable Change
<b>Stain Resistance</b> Distilled Water Orange Peel Lemon Peel Mineral Oil Cloudy Ammonia Chlorox (disinfecting & cleaning) Milk Cola Coffee Tea Ketchup Prepared Mustard Bacon Grease Hamburger Grease	EN 438/2.15 and NEMA LD3.4	No Appreciable Change

### Typical Properties of Panel Substrate

Property	EXTEND Architectural Wall Panels
Surface Treatment	None
Quality	Commercial Type X Gypsum (others available)
Standard Panel Width	48" +/- .025" Standard (others available)
Gypsum Backer	5/8" nom Type X gypsum



### Typical Properties of Stud & Track Components

Property	EXTEND Stud & Track Components
Surface Treatment	Galvannealed ASTM A653 A30 designation
Quality	Cold Rolled Commercial Quality (CRCQ)
Alloy	1018-1020
Steel Gauge	24 gauge
Steel Gauge Tolerance	+/- .0025"
Stud Length	8', 9', 10' standard
Track Length	10' standard



### Typical Properties of Corner & Trim Substrate

Property	EXTEND Corners & Trim
Surface Treatment	Phosphate Type Cleaner
Quality	AA Prime Mill Finish
Alloy/Temper	6061 T3
Aluminum Gauge	Varies by component
Standard Length	10' standard



## Codes and Certifications

### General Standards

EXTEND™ Durable Demising Wall conforms to the standards of the Aluminum Association, Steel Association, and other associations for dimensional tolerance, alloy, temper, performance, and surface appearance specifications.

Property	Test	EXTEND
Sound Transsmission Class (STC)		44-45 est.

### Installation Fabrication and Assembly Recommendations

EXTEND™ Durable Demising Walls can be installed over any flat stable floor surface such as cement, low pile carpet, wood, etc. EXTEND™ Durable Demising Walls can be used as demising walls, room dividers, as decorative perimeter walls, as a traditional gypsum wall replacement, walls in fixtures and display configurations, and other non-load bearing applications. EXTEND™ Durable Demising Walls may not be used as structural members or components.

Installation is completed by securing bottom track to floor through the use of mechanical fasteners such as Tapcon™ style anchors, screws, etc. Top track is plumbed to bottom track and secured to suspended ceiling track or directly to the deck above through use of self tapping screws, etc. Studs are then snapped into top and bottom track with the use of 90 degree stud extenders at each end. Once plumbed to 24" centers, the stud extender brackets are screwed into place with sheet metal style screws. Sound batting is then installed into stud cavity along with stud spacers. Corner pieces are then snapped into studs. Wall is completed by snapping wall panels into studs and trimmed with L or T style trim at the top. Rolled cove base is then used to trim bottom edge at floor. Doors, windows, and utility boxes are cut into EXTEND™ wall panels using suitable jigsaw, spiral saw, etc. Follow the techniques recommended by the saw manufacturer. Horizontal separators can be incorporated into the wall to support a flush-mount whiteboard.

### Warranty

Manufacturer warrants that, EXTEND™ Durable Demising Walls under normal use, will conform to the standards set forth on the EXTEND™ Durable Demising Wall technical data sheets for a period of twelve (12) months from the date of sale to the first consumer purchaser. Manufacturer will also warrant EXTEND™ Durable Demising Wall for a period of (5) years against delamination of the artwork from the steel substrate. In the event that this product does not perform as warranted, the first purchaser's sole remedy shall be limited to repair or replacement of all or any part of the product that is defective, at the manufacturer's sole discretion. This warranty applies only to product in its original installed form from the first consumer buyer. This warranty is not transferable, and expires upon resale or transfer by the first consumer purchaser. This warranty shall not apply to defects or damage arising for any of the following caused by accidents, abuse, improper installation or fabrication, misuse, or failure to properly prepare the bonding surface.



NO OTHER WARRANTIES, EXPRESS OR IMPLIED, ARE MADE. UNDER NO CIRCUMSTANCES SHALL MANUFACTURER BE LIABLE FOR ANY LOSS OR DAMAGE ARISING FROM THE PURCHASE, USE OR INABILITY TO USE THIS PRODUCT, OR FOR ANY SPECIAL, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES. NO FABRICATOR, INSTALLER DEALER AGENT OR EMPLOYEE OF MANUFACTURER HAS THE AUTHORITY TO MODIFY THE OBLIGATIONS OR LIMITATIONS OF THIS WARRANTY.

This warranty gives you specific legal rights, and you also may have other rights that vary from state to state; therefore, some of the limitations stated above may not apply to you. It is to your benefit to save your documentation upon purchase of a product.

### **Care and Maintenance**

The decorative surface may be cleaned with warm water and mild detergents or dishwashing soaps. Do not use cleansers that contain abrasives, they will scratch or damage the decorative surface. Household cleaners such as Fantastick®, 409®, and other like products may be used on stubborn stains. Always test any new cleaner in an inconspicuous spot to ensure no degradation of the surface will occur.

Do not allow any of the following chemicals to remain in prolonged contact with the decorative surface:

- Bleach (except for disinfecting)
- Greater than 10% solutions of, hydrochloric, sulfuric, or nitric acid
- Caustic solutions containing lye (drain cleaners commonly use lye)
- Sodium bisulfate
- Potassium permanganate
- Juice from staining berries
- Violet (genetian)
- Bluing
- Fabric dye
- Alcohol containing iodine
- Hydrogen peroxide solutions

### **Repair and Finishing**

EXTEND™ Durable Demising Walls can be finished with urethane-based topcoats for higher gloss and shine. Finishing steps must be in accordance with the manufacturer's application instructions and performed when the laminate is in its final bonded position. Cracking, crazing, or complete delamination of the topcoat will occur if applied to the laminate sheet prior to bonding or forming. Repair of scratches and gouges can be done through the use of high quality furniture repair kits. Follow repair kit instructions. Avoid repair kits that use an iron in direct contact with the laminate surface as this may increase the gloss level of the finish in that area. Please note that this method will not provide a complete repair if damage is extensive. In such cases, see your local EXTEND™ distributor or [starwallusa.com](http://starwallusa.com) for a replacement panel or trim piece.

### **Technical Questions**

For technical assistance with any of the following technical specifications, please contact us Monday through Friday, 8am-5pm, EST.